


R-1000iA/R-2000iB 系列

R-1000iA/R-2000iB Series

型号 Robot Model	控制器 Controller	控制轴 Controlled Axes	手腕部最大可搬运重量(kg) Max. Load Capacity at Wrist(kg)	重复定位精度(mm) Repeatability (mm)	机构部重量(kg) Mechanical Weight(kg)	运动半径(mm) Reach(mm)	动作范围 Motion Range(*)						最高速度(°/sec) Max. Speed(°/s)						
							J1	J2	J3	J4	J5	J6	J1	J2	J3	J4	J5	J6	
R-1000iA	R-30iA	R-1000iA/80F	6	80	±0.3	620	2230	±180	90~155	-180~180	±360	±125	±360	170	140	160	230	230	350
		R-1000iA/100F	6	100	±0.2	665	2230	360	245	360	720	250	720	130	110	120	170	170	250
		R-2000iB/165F	6	165	±0.3	1170	2655	360	136	362	720	250	720	110	110	110	150	150	220
		R-2000iB/210F	6	210	±0.3	1270	2650	360	136	362	720	250	720	95	90	95	120	120	190
		R-2000iB/250F	6	250	±0.3	1270	2655	360	136	357	720	250	720	95	85	88	120	120	190
		R-2000iB/125L	6	125	±0.3	1190	3005	360	136	352	720	250	720	110	110	110	170	170	260
R-2000iB	R-30iA	R-2000iB/175L	6	175	±0.3	1260	2852	360	136	356	720	250	720	95	90	95	120	120	190
		R-2000iB/185L	6	185	±0.3	1290	3060	360	136	346	720	250	720	95	85	88	120	120	190
		R-2000iB/165SR	6	165	±0.3	1480	3095	360	185	365	720	250	720	110	100	110	150	150	220
		R-2000iB/200R	6	200	±0.3	1540	3095	360	185	365	720	250	720	90	85	95	120	120	190
		R-2000iB/100P	6	100	±0.3	1570	3500	360	185	365	720	250	720	110	90	110	120	120	190
		R-2000iB/100H	5	100/120	±0.2	1150	2655	360	136	362	-	250	720	130	130	130	-	170	360
		R-2000iA/165EW	6	165	±0.3	1400	2650	360	135	208	720	250	440	105	90	105	130	130	210
		R-2000iA/200EW	6	200	±0.3	1510	2650	360	135	208	720	250	440	90	85	90	110	110	155
		R-2000iB/170CF	6	170	±0.15	800	1520	360	190	332	720	250	720	110	110	110	150	150	220
		R-2000iB/150U	6	150	±0.2	1070	2655	360	136	362	720	250	720	110	85	110	150	150	220

可适用领域：高温应用、测量检验、包装、分拣处理、搬运、码垛、灌装、机器上下料、装配、修线、抛光、打磨、水切割、等离子切割、激光焊接于切割、压力装配及铆接、粘接与封接、点焊；



R-2000iB系列



R-1000iA系列

上海发那科机器人有限公司
SHANGHAI-FANUC Robotics Co., Ltd.

