

# **VLS9000**

# Velocity Limiting System For PT9000

### Prevents damage from cable free release.

### Provides safer operation.

Our Velocity Limiting System (VLS) is an option available for our PT9101, PT9150, PT9420, PT9510 and PT9600 cable extension transducers that prevents the measuring cable from ever reaching a damaging velocity during an accidental free release.

This option is ideal for applications that require frequent cable disconnection and reconnection. It prevents expensive unscheduled downtime due to accidental cable mishandling or attachment failure. The guides below define the PT9000 datasheets which support VLS as a Standard Option with quick delivery. Please contact us for availability of datasheets or options not shown.

### Velocity Limiting System Performance Specification

Data Sheets	Measuring Cable Tension Option	Max Retraction Velocity					
PT9101, PT9150,	1 and 3	40 - 55 inches/sec					
PT9420, PT9510, PT9600	2 and 4	40 - 80 inches/sec					
PT9101 Ext Range PT9150 Ext Range PT9420 Ext Range PT9510 Ext Range PT9600 Ext Range	n/a	40 - 55 inches/sec					

#### How to Order

Tel:+086-750-6655202

Find the appropriate PT9000 model shown below on the left and use the corresponding guide to the right to configure the VLS model number. Available options for each model are shown in grey. Consult appropriate PT9000 datasheet for complete description and details of options.

### How to Order

1 low to OI	uei																	
	75 to 550-inch Ranges								600 to 1700-inch Ranges									
	VLS9101 -		·				1		_0_	VLS9101 -		_		_		1		0
PT9101 ▶		0075 0100 0150 0200 0250 0300 0350 0400 0450 0500	1 2 3	1 2	1 2 3	1 2 3 4 5 6	ø	1 2 3 4 5 6 7	•	<b>VL3</b> 9101 -	0600 0800 1000 1200 1500 1700	1	1 2	1 2 3 4	1 2 3 4 5 6	9	1 2 3 4 5 6 7	0
		75 to 5	50₋in	oh D	ango					600 to 1700-inch Ranges								
	75 to 550-inch Ranges VLS9420						_0_	VLS9420-	1 0						0			
		0075	1	1	1	w	1	1	в	V L37420	0600	1	1	1	0	1	1	0
		0100	2		2		2	2			0800		2	2		2	2	
PT9420		0150 0200	3	3	3		3	3			1000 1200			3		3 4	3	
<b>&gt;</b>		0250					5	5			1500					5	5	
		0300 0350					6	6 7			1700					6	6 7	
		0400																
		0450 0500																
		0550																
	<b>VLS</b> 9510 -	75 to 550-inch Ranges								600 to 1700-inch Ranges							^	
	VL39310-	0075	1	1	1	0	1	1	_0_	<b>VLS</b> 9510 -	0600	1	1	1	0	1	1	0
		0100	2	2	2		2	2			0800	3	2	2		2	2	
PT9510 ▶		0150 0200	3	3	3		3 4	3			1000 1200			3		3	3	
		0250	** <b>T</b>	Saute	SU:		5	5			1500			•		5	5	
		0300 0350					6	6 7			1700					6 7	6 7	
		0400					7	1								8	,	
		0450																
		0500 0550																

Tel:+086-750-6655202

	7	5 to 550-in	ch Ran		600 to 1700-inch Ranges							
	VLS9600-						VLS9600-			<u>_</u>	<b>-</b>	
PT9600 ▶		0075	1	1	1	F01		0600	1	1	1	F01
		0100	2	2	2	F02		0800	3	2	2	F02
		0150	3	3	3	S01		1000			3	S01
		0200	4	4	4	S02		1200			4	S02
		0250				S04		1500				S04
		0300						1700				
		0350										
		0400										
		0450										
		0500										
		0550										

Tel:+086-750-6655202