



FS-52

FS Series Flow Sensor

Features

- ◆ Rugged high grade Noryl
- ◆ Minimum pressure drop
- ◆ Operates from a small head of water
- ◆ Mount in any axis
- ◆ Suitable for water and air flow switching

Comments

- ◆ 1¼" BSP female threads
- ◆ Suitable for hot and cold potable water
- ◆ Reed Switch Reliability (UL File E153493)
- ◆ Meets UL 94-HB flammability rating
- ◆ Easy installation

Applications

- ◆ Mains water control
- ◆ Power shower
- ◆ Central heating systems
- ◆ Circulation pump protection
- ◆ Cooling systems

FS-52

FS Series | Flow Sensor

Material

Housing Material	Noryl
Contact Material	Ruthenium
Operating Temperature °C	-30 to 85
Housing Colour	Black

Mechanical Specifications

Shock	50g For A 11ms Duration
Vibration	35g up tp 500Hz
IP	IP65
Switch On Flow Rate L/min	1.5 - 2.0

Switching

Switch Action (Reed Switch)	SPST
Max Switching Voltage VDC	200
Max Switching Voltage VAC	250
Max Switching Current Amps	1
Operate Mode	N/O, Close With Flow
Contact Form	A

Cable

Cable Length	1 x 1.0M double insulated
Connection Type	Stripped Cables
Cable Type	0.5MM2 BS6500 PVC
Cable Colour	Grey

Mounting

Fitting	1 1/4" BSP Thread
Fitment	In Line
Mounting	Any Axis