



FCS-03

FCS Series

Flow Sensor

Features

- ◆ Rugged high grade Noryl
- ◆ Minimum pressure drop
- ◆ Operates from a small head of water
- ◆ Mount in any axis
- ◆ Suitable for water and air flow switching

Comments

- ◆ 3/8" BSP Male threaded fittings
- ◆ Fuels & Oils, Solvents, Organic, Boiling Water, Acids, Organic, Drinking Water (Potable Water), Deionised Water, Acids, Inorganic, Alcohols, Water
- ◆ Reed Switch Reliability File E125629
- ◆ Meets UL 94-HB flammability rating
- ◆ Food grade material

Applications

- ◆ Leak detection
- ◆ Flow sensing
- ◆ Mains water control
- ◆ Cooling systems
- ◆ Circulation pump protection

FCS-03

FS Series | Flow Sensor

Material

Housing Material	PPS
Shuttle Material	PPS
Spring Material	Stainless Steel
Contact Material	Ruthenium
Operating Temperature °C	-30 to 100
Medium	Water
Housing Colour	White

Mechanical Specifications

Shock	50g For A 11ms Duration
Vibration	35g up to 500Hz
Maximum Pressure	10 Bar @ 20°C
IP	IP65
Switch On Flow Rate L/min	0.6

Switching

Switch Action (Reed Switch)	SPST
Max Switching Voltage VDC	200
Max Switching Voltage VAC	250
Max Switching Current Amps	1
Max Switching Load Watt	40
Operate Mode	N/O, Close With Flow
Contact Form	A

Cable

Cable Length	2 x 0.5M single insulated
Connection Type	Stripped Cables
Cable Type	22AWG, 16/0.2mm PVC insulated
Cable Colour	Black/Black

Mounting

Fitting	3/8" BSP Thread
Fitment	In Line
Mounting	Any Axis

Technical Drawing

FCS-03

