

Bench Glossmeter

Introduction:

This small, portable instrument is made for measuring the gloss of curved surface, small pieces, specially shaped surface of small products, application in the area of coatings, automobiles, toys, furniture, plastics, banknotes, teeth, ceramics etc.

Technical info:

- ◆ Angle: 60°
- ◆ Range: 0-2000GU
- ◆ Repeatability: ± 0.5 GU (0-199.9GU)
- ◆ Precision: 1GU
- ◆ Measurement area: 2x2mm
- ◆ Display resolution: 320x240
- ◆ Control: Touch screen with one button measurement
- ◆ Memory: 3000 readings
- ◆ Operation temperature: -10 - 40°C
- ◆ Port: USB
- ◆ Dimension: 220x190x85mm (LxWxH)
- ◆ Weight: 3kg



Features:


- ◆ Automatic calibration
- ◆ One button operation
- ◆ Colorful touch screen displaying readings, statistics and calibration procedure status.
- ◆ Calibration can be done automatically within one second
- ◆ Up to 3000 readings stored.
- ◆ Convenient measurement with infrared sensor switch
- ◆ Foot switch available for simple measurement

Standard:

ASTM D523, DIN 67530

Accessory info:

- BEVS1506/P/001 Standard Calibration
- BEVS1506/P/002 USB Data Cable
- BEVS1506/P/003 Foot switch
- BEVS1506/P/004 Optical Sensor Switch



Order info:

BEVS 1506 Bench Glossmeter
Delivery with 1 x calibration tile, 1 x USB cable, 1 x foot switch and 1 x sensor switch