

# Digital Adjustable Applicator

## ■ Introduction:

The Adjustable Digital Applicator is designed according to ASTM D823E. It consists of two precise digital micrometers, a high precise scraper and a special alumina frame.

## ■ Technical info:

- ◆ Made of stainless steel with high wear resistance
- ◆ 5 film widths are available: 100/150/200/250/300 mm
- ◆ Precision:  $\pm 2\mu\text{m}$
- ◆ Film thickness range: 0-3500 $\mu\text{m}$
- ◆ In 1 $\mu\text{m}$  increment



## ■ Order info:

| Name                          | Model          | Film Width(mm) | Note                     |
|-------------------------------|----------------|----------------|--------------------------|
| Digital Adjustable Applicator | BEVS 1806F/100 | 100            | Without diversion baffle |
|                               | BEVS 1806F/150 | 150            |                          |
|                               | BEVS 1806F/200 | 200            |                          |
|                               | BEVS 1806F/250 | 250            |                          |
|                               | BEVS 1806F/300 | 300            |                          |
| Digital Adjustable Applicator | BEVS 1806E/100 | 100            | With diversion baffle    |
|                               | BEVS 1806E/150 | 150            |                          |
|                               | BEVS 1806E/200 | 200            |                          |
|                               | BEVS 1806E/250 | 250            |                          |
|                               | BEVS 1806E/300 | 300            |                          |