

Series 4100 系列

Cross Cut Routers 棱形齿锣刀

Updraft Design for superior tool life and exceptional edge finish

向上排尘设计, 寿命出众的边切割成型加工

Diameter 直径 : 0.50 mm - 3.175mm



| Series 钻咀系列 | Size 钻咀直径 | | Flute Length 刃长 (mm) | Part Number (FT) 产品编号(鱼尾) | Part Number(DP) 产品编号(钻尖) |
|----------------|-----------|--------|-------------------------|------------------------------|-----------------------------|
| | (mm) | (inch) | | | |
| 4100 | 0.50 | 0.0197 | 2.00 | 4100.0197.079 | - |
| 4100 | 0.60 | 0.0236 | 3.00 | 4100.0236.118 | - |
| 4100 | 0.80 | 0.0315 | 5.00 | 4100.0315.197 | 4100.0315.197D |
| 4100 | 0.80 | 0.0315 | 6.50 | 4100.0315.256 | - |
| 4100 | 0.90 | 0.0354 | 5.00 | 4100.0354.197 | 4100.0354.197D |
| 4100 | 0.90 | 0.0354 | 6.50 | 4100.0354.256 | - |
| 4100 | 1.00 | 0.0394 | 5.00 | 4100.0394.197 | - |
| 4100 | 1.00 | 0.0394 | 7.00 | 4100.0394.276 | 4100.0394.276D |
| 4100 | 1.10 | 0.0433 | 5.00 | 4100.0433.197 | - |
| 4100 | 1.10 | 0.0433 | 7.00 | 4100.0433.276 | 4100.0433.276D |
| 4100 | 1.20 | 0.0472 | 5.00 | 4100.0472.197 | - |
| 4100 | 1.20 | 0.0472 | 7.00 | 4100.0472.276 | - |
| 4100 | 1.30 | 0.0512 | 5.00 | 4100.0512.197 | - |
| 4100 | 1.30 | 0.0512 | 7.00 | 4100.0512.276 | - |
| 4100 | 1.40 | 0.0551 | 6.50 | 4100.0551.256 | 4100.0551.256 |
| 4100 | 1.40 | 0.0551 | 8.00 | 4100.0551.315 | - |
| 4100 | 1.50 | 0.0591 | 6.50 | 4100.0591.256 | 4100.0591.256D |
| 4100 | 1.50 | 0.0591 | 8.00 | 4100.0591.315 | - |
| 4100 | 1/16" | 0.0625 | 8.00 | - | 4100.0625.315D |
| 4100 | 1.60 | 0.0630 | 6.50 | 4100.0630.256 | - |
| 4100 | 1.60 | 0.0630 | 8.00 | 4100.0630.315 | - |
| 4100 | 1.70 | 0.0669 | 8.00 | 4100.0669.315 | - |
| 4100 | 1.80 | 0.0709 | 8.00 | 4100.0709.315 | 4100.0709.315D |
| 4100 | 1.90 | 0.0748 | 8.00 | 4100.0748.315 | 4100.0748.315D |
| 4100 | 2.00 | 0.0787 | 8.00 | 4100.0787.315 | 4100.0787.315D |
| 4100 | 2.00 | 0.0787 | 10.00 | 4100.0787.394 | - |
| 4100 | 2.10 | 0.0827 | 10.00 | - | 4100.0827.394D |
| 4100 | 2.20 | 0.0866 | 10.00 | 4100.0866.394 | - |
| 4100 | 2.30 | 0.0906 | 10.00 | 4100.0906.394 | 4100.0906.394D |
| 4100 | 3/32" | 0.0938 | 10.00 | - | 4100.0938.394D |
| 4100 | 2.40 | 0.0945 | 10.00 | 4100.0945.394 | - |
| 4100 | 2.50 | 0.0984 | 10.00 | 4100.0984.394 | 4100.0984.394D |
| 4100 | 2.55 | 0.1004 | 10.00 | 4100.1004.394 | 4100.1004.394D |
| 4100 | 3.00 | 0.1181 | 10.00 | 4100.1181.394 | - |
| 4100 | 3.10 | 0.1220 | 10.00 | 4100.1220.394 | - |
| 4100 | 3.175 | 0.1250 | 12.00 | 4100.1250.472 | 4100.1250.472D |